

ProLiner™ Banded Liner System Banding

Technical Data Sheet

Description

Therm-All's ProLiner™ banding is a steel strapping used to support the liner system's vapor retarder and unfaced fiberglass blanket insulation in roof and wall applications on the interior of metal buildings.

Features

- Hot dipped galvanized product made from high strength steel.
- Ribbon wound coils shipped to jobsite pre-loaded on wooden dispensers from easy pay-out.
- Designed to provide elongation before breaking in the event of a fall at the roof's leading edge.

Applications

- For use in liner system roof and wall applications. For roof, can be supplied and installed in either a bi-directional patten (fall protection version) or a single direction pattern (non-fall protection version).

Technical Data

Size:	1" x 500' coils 1" x 1,250' coils
Steel:	ASTM A 653/A 653M-17
Coating:	G-40 coating weight
Grade:	Structural Steel Grade 60
Yield Strength:	60,000 PSI minimum
Tensile Strength:	70,000 PSI minimum
Colors:	White, black, gray to match

Disclaimer of Liability

Users should test each product for suitability for their specific purposes since Therm-All has no control over methods of application or conditions of use. THERM-ALL MAKES NO EXPRESS OR IMPLIED WARRANTIES OF ANY KIND INCLUDING MERCHANTABILITY except that products shall be of standard commercial grade to meet our specifications.
